

MII-4010-400KV



Lipo	PROP	V	A	RPM	THRUST (g)	Recommend flight weight(g)	Recommend flight weight(g)	Recommend flight weight(g)	Recommend flight weight(g)
3S	TL2829 13*5.5	11.1	5.05	3995	600	900	1200	1800	2400
	TL2830 14*5.5	11.1	6.61	3861	750	1125	1500	2250	3000
	TL2831 15*5.5	11.1	9.05	3635	1150	1725	2300	3450	4600
	TL2813 15*5.5	11.1	6.94	3852	900	1350	1800	2700	3600
	TL2834 15*7.5	11.1	6.2	3889	800	1200	1600	2400	3200
	TL2814 16*5.0	11.1	12.5	3376	1050	1575	2100	3150	4200
	TL2835 16*5.5	11.2	11.2	3497	1100	1650	2200	3300	4400
	TL2815 17*5.5	11.3	10.28	3613	1300	1950	2600	3900	5200
TL2822 18*5.5	11.3	13.7	3327	1550	2325	3100	4650	6200	
Lipo	PROP	V	A	RPM	THRUST (g)				
4S	TL2828 12*5.5	14.9	5.78	5361	750	1125	1500	2250	3000
	TL2829 13*5.5	14.9	8.13	5114	850	1275	1700	2550	3400
	TL2830 14*5.5	14.9	10.57	4894	975	1462.5	1950	2925	3900
	TL2831 15*5.5	14.7	13.95	4516	1300	1950	2600	3900	5200
	TL2813 15*5.5	14.9	10.66	4894	1125	1687.5	2250	3375	4500
	TL2834 15*7.5	14.9	10.18	4919	1050	1575	2100	3150	4200
	TL2814 16*5.0	14.7	19	4063	1400	2100	2800	4200	5600
	TL2835 16*5.5	14.8	17.4	4274	1475	2212.5	2950	4425	5900
	TL2815 17*5.5	14.9	15.7	4416	1600	2400	3200	4800	6400
	TL2822 18*5.5	14.8	20.16	4052	1850	2775	3700	5550	7400
Lipo	PROP	V	A	RPM	THRUST (g)				
5S	TL2828 12*5.5	18.6	8.3	6463	1100	1650	2200	3300	4400
	TL2829 13*5.5	18.5	11.97	6075	1500	2250	3000	4500	6000
	TL2830 14*5.5	18.6	15.45	5776	1850	2775	3700	5550	7400
	TL2831 15*5.5	18.5	20	5322	2250	3375	4500	6750	9000
	TL2813 15*5.5	18.5	14.9	5815	1950	2925	3900	5850	7800
	TL2834 15*7.5	18.5	14.6	5824	1900	2850	3800	5700	7600
	TL2814 16*5.0	18.4	28.4	4573	2100	3150	4200	6300	8400
	TL2835 16*5.5	18.5	24.4	4956	2250	3375	4500	6750	9000
	TL2815 17*5.5	18.5	22.02	5165	2550	3825	5100	7650	10200
	TL2822 18*5.5	18.4	27.18	4713	2950	4425	5900	8850	11800
Lipo	PROP	V	A	RPM	THRUST (g)				
6S	TL2826 10*5.5	22.2	5.17	8150	825	1237.5	1650	2475	3300
	TL2827 11*5.5	22.3	8.6	7796	1200	1800	2400	3600	4800
	TL2828 12*5.5	22.2	11.4	7463	1500	2250	3000	4500	6000
	TL2829 13*5.5	22.2	16.22	6973	2000	3000	4000	6000	8000
	TL2830 14*5.5	22.2	20.84	6581	2450	3675	4900	7350	9800
	TL2831 15*5.5	22.2	26.7	6025	3000	4500	6000	9000	12000
	TL2813 15*5.5	22.3	19.7	6694	2550	3825	5100	7650	10200
	TL2834 15*7.5	22.2	19.6	6640	2500	3750	5000	7500	10000
TL2815 17*5.5	22.2	29.1	5810	3300	4950	6600	9900	13200	