

Item No.	Prop	Throttle %	V	A	RPM	Thrust (G)	Power (W)	Efficiency(G/W)	
M-2204-2300kv	Dal 5040 (3S)	50%	11.1	3.33	13075	165	36.963	4.46	
	Dal 5040 (3S)	65%	11.1	4.54	14913	211	50.394	4.19	
	Dal 5040 (3S)	75%	11.1	5.65	16251	252	62.715	4.02	
	Dal 5040 (3S)	85%	11.1	7.4	17823	309	82.14	3.76	
	Dal 5040 (3S)	100%	11.1	8.72	18961	346	96.792	3.57	
	Dal 5040 (4S)	50%	14.8	4.7	16253	254	69.56	3.65	
	Dal 5040 (4S)	65%	14.8	6.3	18085	317	93.24	3.40	
	Dal 5040 (4S)	75%	14.8	8.11	19832	386	120.028	3.22	
	Dal 5040 (4S)	85%	14.8	10.54	21446	463	155.992	2.97	
	Dal 5040 (4S)	100%	14.8	12.82	23244	533	189.736	2.81	
	HQ 5045 (3S)	50%	11.1	3.95	10716	192	43.845	4.38	
	HQ 5045 (3S)	65%	11.1	6.13	12686	273	68.043	4.01	
	HQ 5045 (3S)	75%	11.1	8.33	14121	340	92.463	3.68	
	HQ 5045 (3S)	85%	11.1	10.93	15478	410	121.323	3.38	
	HQ 5045 (3S)	100%	11.1	13.2	16583	462	146.52	3.15	
	HQ 5045 (4S)	50%	14.8	5.36	13006	286	79.328	3.61	
	HQ 5045 (4S)	65%	14.8	8.53	15312	401	126.244	3.18	
	HQ 5045 (4S)	75%	14.8	11.8	16687	491	174.64	2.81	
	HQ 5045 (4S)	85%	14.8	15.61	18295	586	231.028	2.54	
	HQ 5045 (4S)	100%	14.8	18.49	19083	657	273.652	2.40	
	DAL 6040 (3S)	50%	11.1	4.12	10471	213	45.732	4.66	
	DAL 6040 (3S)	65%	11.1	6.5	12373	308	72.15	4.27	
	DAL 6040 (3S)	75%	11.1	8.93	13710	384	99.123	3.87	
	DAL 6040 (3S)	85%	11.1	11.78	15023	464	130.758	3.55	
	DAL 6040 (3S)	100%	11.1	13.89	15991	512	154.179	3.32	
DAL 6040 (4S)	50%	14.8	5.56	12470	311	82.288	3.78		
DAL 6040 (4S)	65%	14.8	9.08	14759	447	134.384	3.33		
DAL 6040 (4S)	75%	14.8	12.45	16251	532	184.26	2.89		
DAL 6040 (4S)	85%	14.8	15.76	17645	622	233.248	2.67		
DAL 6040 (4S)	100%	14.8	19.75	18892	752	292.3	2.57		