

M-2208-2000KV

Lipo	Prop	Throttle	V	A	RPM	THRUST (g)
4S	GEMFAN 4045	50%	18.81	4.23	22374	150
		65%	18.81	4.98	24011	200
		75%	18.81	5.4	24936	225
		85%	18.81	6.19	26229	250
		100%	18.81	6.47	26955	275
	HQPROP 4*4.5	50%	14.8	6.61	18142	225
		65%	14.8	8.52	20094	275
		75%	14.8	9.47	21010	325
		85%	14.8	11.24	22592	400
		100%	14.79	13.03	23881	450
	FC 5*4.5	50%	14.8	7.21	17409	300
		65%	14.81	9.21	19160	400
		75%	14.8	10.95	20149	450
		85%	14.81	14.31	22428	550
		100%	14.81	15.33	22997	575
	HQPROP 6*4.5	50%	14.81	10.71	4808	450
		65%	14.82	15.88	5815	625
		75%	14.84	21.29	6285	775
		85%	14.81	26.73	7010	950
		100%	14.81	30.78	7575	1000
FC 6*4.5	50%	140.81	8.87	14000	425	
	65%	14.81	13.3	16100	600	
	75%	14.81	16.15	17528	700	
	85%	14.8	22.54	19613	900	
	100%	14.8	24	19998	950	
FC 3 Blades 5*4.5	50%	14.81	8.06	15994	375	
	65%	14.81	10.63	17680	450	
	75%	14.81	13.69	19459	550	
	85%	14.82	17.88	21641	650	
	100%	14.81	19.21	21820	700	